

HEAVY Protection - T10



Type: T10

This system applies to high risk applications following the STD EN 294, tab 2. The welded mesh size is 20x100 mm allows the protection to be mounted at a distance of 120 mm from the dangerous equipment.

Advantages:

- Fast and easy assembly.
- Floor/platform mounting with adjustment post of +/- 50mm.
- Compatible with the other panels or doors in the Tivox Safety Range.
- Few components.
- Strong and durable.
- Competitively priced.
- Aesthetically pleasing.
- Good visibility.

Application examples:

- Special machinery
- Robots
- Conveyors Systems

Technical Information

Panel Type: T10

Posts: 60X60

The panels 100 x 20mm mesh is welded to a pre-drilled tube frame 30x30 mm as well as a central horizontal strengthening bar.

Height mm	Wide mm	Weight kg
H 1500	200	5,20
	300	6,60
	700	9,40
	800	10,10
	1000	11,40
	1200	13,70
	1500	16,20
H 1900	200	6,30
	300	7,20
	500	9,10
	700	11,30
	800	12,40
	1000	14,00
	1200	16,10
H 2500	200	8,60
	300	9,70
	700	15,50
	800	16,70
	1000	19,20
	1200	21,20

Special sizes available

Height of protection:	1700/2100/2700 mm
Post:	60x60x2 mm
Fixing foot:	170x100 mm
Height from ground:	200 mm
Color:	Standard black RAL 9005. Other colours to order.

Options/Accessories

- Plastic caps for top of posts.
- Cutting kit for horizontal panels.
- Cutting kit for vertical panels.
- Protection rubber for cut panels.
- Hinge kits to angle panels.



Profile 30x30x1,5 mm
Mesh 20x100 mm
Wire 3 mm



Fixing foot with adjustment of +/- 50 mm. Pre-assembly.